

What drives **Thunder plus 150 kW Fast Charge**

| | |
|--|---|
| Rating | 150 kW |
| No of Output / Connector | 2 |
| Output Supply | DC |
| Output Voltage max | 200 - 1000 Volts DC |
| Input Supply | Three Phase 400-460 Volts, 5 wire system L1-L2-L3-N-E |
| Charging Mode | Mode 3 |
| Connector Type | CCS2 |
| Maximum Cord length meter | 5 Meter |
| Each vehicle Maximum Input Power | 150 kW |
| Installation Type | Plinth Mount |
| App-based monitoring and tracking | GSM / Wifi |
| Efficiency | Greater than 95% |
| Input Supply Power Factor Greater | Greater than 0.97 |
| Ingress Protection | IP55 |
| Impact Resistance Protection | IK10 |
| Communication | OCPP 1.6 J or higher |
| Compatible to Charge | Car, Minitruck, Minibus, Bus, Truck |
| Protection | |
| Over Voltage, Under Voltage, Over Current, Over Temperature, Under Temperature, Short Circuit, Residual Current, Earth Fault, Hardware Fault | |



EASY INSTALLATION. GREAT FEATURES.



Highly economical



NABL-approved LEV DC charger



Compact and easy installation



Free installation and maintenance



Suits all weather conditions



App-based monitoring and tracking



On-call customer support